

ALPHA 2100

Non-Sag Sealant

UPDATED 12/9/19

Product Overview: ALPHA 2100 is a one part, non-sag sealant designed to prevent air and moisture intrusion. This product is formulated specifically to withstand all weather conditions. ALPHA 2100 adheres to a variety of substrates, and is paintable.

Product Uses: As a non-sag sealant, ALPHA 2100 is well-suited for applications that involve , vertical surfaces. Once cured, ALPHA 2100 withstands the shock, vibration, and stress of outdoor transportation. Adheres to most building materials.

Technical Information:

Raw Material Base	Thermoplastic Rubber	Odor	Mild Solvent
Viscosity	Non-Sag	Water Penetration	None
Color	Clear, White, Gray, Beige, Black	Service Temp. Range	-30° – 200°F
Specific Gravity	0.80 – 0.90	Application Temp. Range	0° – 120°F
Solids	64%		Surface temperature
Coverage	380 Lineal Ft./Gallon	Manufactured State	Tubes, Chubs
Low Temp. Flexibility	No Adverse Effects	Shelf Life	12 Months

Application Information: Ensure substrates are clean, dry, and free of oil and moisture. Exercise care during application to prevent air or contaminant entrapment. This product can be applied by standard hand or air-powered caulking guns. A skin develops typically in 10-20 minutes after application.

Safety Instructions: CAUTION! This product contains solvent. Keep away from sparks, heat, and open flame. Overexposure can cause nausea. Consult the product SDS for detailed safety information.

Contact Us: For more information regarding this product and others, please contact us at:

Alpha Systems LLC
5120 Beck Drive
Elkhart, IN 46516

Phone: 1-574-295-5206
Fax: 1-574-970-2703
www.alphallc.us

RESIDENTIAL HOUSING · RVS/UTILITY TRAILER · HVAC ·
COMMERCIAL/INDUSTRIAL ROOFING · MARINE · MOBILE/MODULAR · METAL BUILDING

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Alpha Systems control are such that Alpha Systems assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.